

The Opening Vent Rooflight

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium Fully Thermally Broken Polyester Powder Coating to Minimum 60 Microns Suitable for Marine / Coastal Environments Stainless Steel Concealed Fixings Tested in accordance with the CWCT Standard Air & Water Resistance 1050pa Wind Load Resistance 2.0kN/m²



Usage:

Suitable for all nominally flat roof constructions and coverings e.g., Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material. Suitable for Green / Sedum Roofs

Product Guidance

Standard Sizes

(mm)	Height	800	1000	1200	1400
Width (Upto)					
1000		~	~	✓	×
1200		✓	✓	✓	 Image: A second s
1400		✓	✓	✓	 Image: A set of the set of the
1700		✓	✓	✓	 Image: A set of the set of the
2200		✓	✓	✓	

Non-standard sizes and shapes are available on request

NB: These are external kerb sizes.

Internal finished sizes; minus 200mm from above Width & Height dimensions



Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Vision AGI Limited, Company No. 08429446, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HF.



Standard Glazing Details: 6mm Toughened Outer 18mm Warm Edge Spacer with 90% Argon Cavity 8.8mm Laminate Low-e Inner Glass Centre Pane U-Value 1.1W/m²K

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain and decorative options are available, please contact manufacturer for details.

Alternative non-glazed fillings such as insulated panels are available on request.

Standard Colour:

Internal – RAL 9010 Pure White Matt External – RAL 7015 Slate Grey Matt

Any RAL or BS colour can be specified.

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant EPDM – UV & Water Resistant

Operation:

Manual or Electric, Wind, Rain & Temperature Sensors for auto-closing. Remote Control

Upstand:

To suit an overall finished Upstand of 100mm in width. Upstand by Next Generation Rooflights if required.

Warranty: 1 Year offered as standard. Extended warranty available as below, upon registration.

Glazing 10 Years Powder Coating 10 Years Mechanical Components 1 Year



Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223792244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Vision AGI Limited, Company No. 08429446, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HE.



Product Specification

Manufacturer:

Name:	Next Generation Rooflights
Web:	www.nextgenrooflights.co.uk
Email:	info@nextgenrooflights.co.uk
Tel:	+44 (0)1223 79 22 44
Address:	Queens Business Park, Wilbraham Road, Fulbourn, Cambridge, CB21 5GT
Product reference:	The Opening Rooflight

Other Rooflights in the Range

Fixed Skylight

Access Hatch Rooflight - Manual Access Hatch Rooflight - Electric

Walk On Glass Floor – Internal Use Walk On Glass Floor – External Use

Pyramid Rooflight Pyramid Rooflight – Manual Pyramid Rooflight – Electric

Lantern Rooflight Lantern Rooflight – Manual Lantern Rooflight – Electric

Slide Over Roof Rooflight Slide Over Fixed Rooflight Bi-Parting Slide Over Roof Rooflight Bi-Parting Slide Over Fixed Rooflight Roof Access Door



Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Vision AGI Limited, Company No. 08429446, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HF.