

The Walk On **Glass Floor - Internal**

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium Polyester Powder Coating to Minimum 60 Microns BS EN 1991-1 1.5kN/m2 UDL & 2.0kN/m2 Concentrated Load Commercial Loading available by request (Domestic loading)



Suitable for all floor constructions and coverings e.g. timber, tiled, stone etc.

Product Guidance

Standard Sizes

(mm)	Height	1000	1200	1400
Width				
1000		✓	✓	✓
1200		✓	✓	✓
1400		✓	✓	✓

Non-standard sizes and shapes are available on request

Standard Glazing Details:

12mm Toughened / 1.52mm PVB Interlayer / 12mm Toughened Outer

Enhanced glazing specifications incorporating Anti slip, thermal, acoustic, security, light transmission and decorative options are available, please contact manufacturer for details.

Standard Colour:

Ral 9005 Matt

Any RAL or BS colour can be specified Anodised options

Seals:

Structural & Perimeter Seal - Low Modulus Silicone Sealant





Warranty:

1 Year offered as standard. Extended warranty available as below, upon registration.

Glazing 10 Years Powder Coating 10 Years

Product Specification

Manufacturer:

Name: **Next Generation Rooflights**

Web: www.nextgenrooflights.co.uk

Email: info@nextgenrooflights.co.uk

+44 (0)1223 79 22 44 Tel:

Address: Queens Business Park, Wilbraham Road, Fulbourn,

Cambridge, CB21 5GT

The Walk On Glass Floor - Internal Product reference:

Other Rooflights in the Range

Fixed Skylight

Access Hatch Rooflight - Manual Access Hatch Rooflight - Electric

Opening Rooflight - Electric Opening Rooflight - Manual

Walk On Glass Floor - External use

Pyramid Rooflight

Pyramid Rooflight - Manual Pyramid Rooflight - Electric

Lantern Rooflight

Lantern Rooflight - Manual Lantern Rooflight – Electric

Slide Over Roof Rooflight Slide Over Fixed Rooflight Bi-Parting Over Rooflight Bi-Parting Over Fixed Rooflight Access Rooflight Door



Next Generation Rooflights