



The Pyramid & Lantern Rooflights - Fixed

Detailed Description

Features: Grade 6063-T6 Extruded Aluminium Fully Thermally Broken Polyester Powder Coating to Minimum 60 Microns Suitable for Marine / Coastal Environments Stainless Steel Concealed Fixings Tested in accordance with the CWCT Standard Air & Water Resistance 1050pa Wind Load Resistance 2.0kN/m²

Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material. Suitable for Green / Sedum Roofs

Product Guidance

Standard Sizes

| (mm) | Height | 1000 | 1200 | 1400 | 1500 | 1700 | 2000 | 2200 |
|-------|--------|----------|----------|----------|----------|----------|--|--|
| Width | | | | | | | | |
| 1000 | | ~ | × | × | ~ | × | × | √ |
| 1200 | | √ | × | × | ✓ | √ | ✓ | ✓ |
| 1400 | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 1500 | | ~ | ~ | × | ~ | ✓ | ✓ | × |
| 1700 | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 2000 | | ✓ | ~ | ✓ | ✓ | ~ | ~ | ~ |
| 2200 | | √ | √ | √ | √ | √ | Image: A second s | Image: A second s |

Non-standard sizes and shapes are available on request.

NB: These are external kerb sizes. Internal finished sizes; minus 200mm from above Width & Height dimensions



Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk



Standard Glazing Details:

6mm Toughened Outer 18mm Warm Edge Spacer with 90% Argon Cavity 8.8mm Laminate Low-e Inner Glass Centre Pane U-Value 1.1W/m²K

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain and decorative options are available, please contact manufacturer for details.

Standard Colour:

Internal – RAL 9010 Pure White Matt External – RAL 7015 Slate Grey Matt

Any RAL or BS colour can be specified

Seals: Structural & Weather Seal – Low Modulus Silicone Sealant EPDM – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 100mm in width. Upstand by Next Generation Rooflights if required.

Warranty: 1 Year offered as standard. Extended warranty available as below, upon registration.

Glazing 10 Years Powder Coating 10 Years Mechanical Components 1 Year



Next Generation Rooflights

Queens Business Park, Wilbraham Ro<mark>ad, Fulbourn, Cambr</mark>idge CB<mark>21 5G</mark>T

01223 792 244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk



Product Specification

| Manufacturer: | | | |
|--------------------|---|--|--|
| Name: | Next Generation Rooflights | | |
| Web: | www.nextgenrooflights.co.uk | | |
| Email: | info@nextgenrooflights.co.uk | | |
| Tel: | +44 (0)1223 79 22 44 | | |
| Address: | Queens Business Park, Wilbraham Rd, Fulbourn, Cambridge | | |
| | | | |
| Product reference: | The Pyramid & Lantern Rooflights - Fixed | | |

Other Rooflights in the Range

Fixed Skylight

Access Hatch Rooflight - Manual Access Hatch Rooflight - Electric

Opening Rooflight – Electric Opening Rooflight – Manual

Walk On Glass Floor – Internal Use Walk On Glass Floor – External Use

Pyramid Rooflight – Manual Pyramid Rooflight – Electric

Lantern Rooflight – Manual Lantern Rooflight – Electric

Slide Over Roof Rooflight Slide Over Fixed Rooflight Bi-Parting Slide Over Roof Rooflight Bi-Parting Slide Over Fixed Rooflight Roof Access Door



Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk