

Sliding Rooflight (Slide Over Fixed Rooflight)

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium
Fully Thermally Broken
Polyester Powder Coating to Minimum 60 Microns
Suitable for Marine / Coastal Environments
Stainless Steel Concealed Fixings
Air permeability – Class 4
Water tightness – Class E1050
Wind resistance – Class C5



Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material. Suitable for Green / Sedum Roofs

Product Guidance

Up to 6100mm (external **Width**) in the sliding direction Up to 4000mm (external **Span**) down the fall

Wide range of sizes available

NB: These are external kerb sizes. Internal finished sizes; minus 300mm from above Width & Height dimensions

Typical Glazing Details:

6mm Toughened Outer 18mm Warm Edge Spacer with 90% Argon Cavity 8.8mm Laminate Low-e Inner

Glass Centre Pane U-Value 1.1W/m²

Standard Colour:

Internal – RAL 9010 Pure White Matt External – RAL 7015 Slate Grey Matt



Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT





Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant PVC coated – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 150mm. Upstand by Next Generation Rooflights if required.

Warranty:

1 Year offered as standard. Extended warranty available as below, upon registration.

Glazing 10 Years Powder Coating 10 Years Mechanical Components 1 Year

Options

Operation:

Access keypad Rain Sensor Temperature sensor Control by Smartphone

Size:

Non-standard sizes are available on request.

Colour:

Any RAL or BS colour can be specified

Glazing Details:

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain and decorative options are available, please contact manufacturer for details.





Product Specification

Manufacturer:

Name: Next Generation Rooflights

Web: www.nextgenrooflights.co.uk

Email: info@nextgenrooflights.co.uk

Tel: +44 (0)1223 79 22 44

Address: Queens Business Park, Wilbraham Road, Fulbourn,

Cambridge, CB21 5GT

Product reference: Bi-Parting Slide Over Fixed Rooflight

Other Rooflights in the Range

Fixed Skylight

Opening Rooflight – Manual Opening Rooflight – Electric

Walk On Glass Floor – Internal Use Walk On Glass Floor – External Use

Pyramid Rooflight

Pyramid Rooflight – Manual Pyramid Rooflight – Electric

Lantern Rooflight

Lantern Rooflight – Manual Lantern Rooflight – Electric

Access Hatch Rooflight - Manual Access Hatch Rooflight - Electric

Slide Over Roof Rooflight Bi-Parting Slide Over Fixed Rooflight Bi-Parting Slide Over Roof Rooflight Roof Access Door

