

Circular Walk On Glass Floors - External

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium Fully Thermally Broken Polyester Powder Coating to Minimum 60 Microns

Suitable for Marine / Coastal Environments Stainless Steel Concealed Fixings Tested in accordance with the CWCT Standard Air & Water Resistance 1050pa Wind Load Resistance 2.0kN/m² BS EN 1991-1 1.5kN/m2 UDL & 2.0kN/m2 PL



Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material. Suitable for Green / Sedum Roofs

Product Guidance

As Standard:

Standard Sizes (25mm outer) upto 1250mm Diameter Standard Sizes (33mm outer) upto 2450mm Diameter

NB: These are external kerb sizes.

Internal finished sizes; minus 230mm from above Width & Height dimensions

Glazing Details (upto 1250mm):

12mm Toughened / 1.52mm PVB Interlayer / 12mm Toughened Outer 16mm Warm Edge Spacer with 90% Argon Cavity 6mm Toughened Low-e Inner Glass Centre Pane U-Value 1.1W/m²K

Glazing Details (upto 2450mm):

10mm TGH / 1.52mm PVB / 10mm TGN / 1.52mm PVB/ 10mm TGN Outer 16mm Warm Edge Spacer with 90% Argon Cavity 8mm Toughened Low-e Inner Glass Centre Pane U-Value 1.1W/m²K



Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223792244 info@nextgenrooflights.co.uk www.nextgenrooflights.co.uk





Colour:

Internal – RAL 7015 Slate Grey Matt External – RAL 7015 Slate Grey Matt

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant FPDM – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 115mm. Upstand by Next Generation Rooflights if required.

Warranty:

1 Year offered as standard. Extended warranty available as below, upon registration.

Glazing 10 Years Powder Coating 10 Years

Options

Size:

Non-standard sizes and shapes are available on request.

Colour:

Any RAL or BS colour can be specified

Glazing Details:

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain and decorative options are available, please contact manufacturer for details.

Frame Material:

Different material specifications stainless steel cladding etc are available please contact manufacturer for details.





Product Specification

Manufacturer:

Name: Next Generation Rooflights

Web: www.nextgenrooflights.co.uk

Email: info@nextgenrooflights.co.uk

Tel: +44 (0)1223 79 22 44

Address: Queens Business Park, Wilbraham Road, Fulbourn

Cambridge, CB21 5GT

Product reference: The Walk-On Glass Floor - External

Other Rooflights in the Range

Fixed Skylight

Access Hatch Rooflight - Manual Access Hatch Rooflight - Electric

Opening Rooflight – Electric Opening Rooflight – Manual

Roof Access Door

Walk On Glass Floor - Internal Use

Pyramid Rooflight

Pyramid Rooflight – Manual Pyramid Rooflight – Electric

Lantern Rooflight

Lantern Rooflight – Manual Lantern Rooflight – Electric

Slide Over Roof Rooflight Slide Over Fixed Rooflight Bi-Parting Slide Over Roof

Bi-Parting Slide Over Roof Rooflight Bi-Parting Slide Over Fixed Rooflight

