

The Opening Vent Rooflight

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium
Fully Thermally Broken
Polyester Powder Coating to Minimum 60 Microns
Suitable for Marine / Coastal Environments
Stainless Steel Concealed Fixings
Tested in accordance with the CWCT Standard
Air & Water Resistance 1050pa
Wind Load Resistance 2.0kN/m²

Usage:

Suitable for all nominally flat roof constructions and coverings e.g., Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material.
Suitable for Green / Sedum Roofs



Product Guidance

Standard Sizes

| (mm) | Height | 800 | 1000 | 1200 | 1400 |
|----------------------|--------|-----|------|------|------|
| Width (Up to) | | | | | |
| 1000 | | ✓ | ✓ | ✓ | ✓ |
| 1200 | | ✓ | ✓ | ✓ | ✓ |
| 1400 | | ✓ | ✓ | ✓ | ✓ |
| 1700 | | ✓ | ✓ | ✓ | ✓ |
| 2200 | | ✓ | ✓ | ✓ | |

Non-standard sizes and shapes are available on request

NB: These are external kerb sizes.

Internal finished sizes; minus 200mm from above Width & Height dimensions

Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 | info@nextgenrooflights.co.uk | www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Next Gen Rooflights Limited.

Company No. 08429446, VAT No. 169 7051 80, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HF.



Standard Glazing Details:

6mm Toughened Outer
18mm Warm Edge Spacer with 90% Argon Cavity
8.8mm Laminate Low-e Inner
Glass Centre Pane U-Value 1.1W/m²K

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain and decorative options are available, please contact manufacturer for details.

Alternative non-glazed fillings such as insulated panels are available on request.

Standard Colour:

Internal – RAL 9010 Pure White Matt
External – RAL 7015 Slate Grey Matt

Any RAL or BS colour can be specified.

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant
EPDM – UV & Water Resistant

Operation:

Manual or Electric, Wind, Rain & Temperature Sensors for auto-closing. Remote Control

Upstand:

To suit an overall finished Upstand of 100mm in width. Upstand by Next Generation Rooflights if required.

Warranty:

1 Year offered as standard.
Extended warranty available as below, upon registration.

Glazing 10 Years
Powder Coating 10 Years
Mechanical Components 1 Year



Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 | info@nextgenrooflights.co.uk | www.nextgenrooflights.co.uk



**NEXT
GENERATION
ROOFLIGHTS**

Product Specification

Manufacturer:

Name: Next Generation Rooflights
Web: www.nextgenrooflights.co.uk
Email: info@nextgenrooflights.co.uk
Tel: +44 (0)1223 79 22 44
Address: Queens Business Park, Wilbraham Road, Fulbourn,
Cambridge, CB21 5GT
Product reference: The Opening Rooflight

Other Rooflights in the Range

Fixed Skylight

Access Hatch Rooflight - Manual
Access Hatch Rooflight - Electric

Walk On Glass Floor - Internal Use
Walk On Glass Floor - External Use

Pyramid Rooflight
Pyramid Rooflight - Manual
Pyramid Rooflight - Electric

Lantern Rooflight
Lantern Rooflight - Manual
Lantern Rooflight - Electric

Slide Over Roof Rooflight
Slide Over Fixed Rooflight
Bi-Parting Slide Over Roof Rooflight
Bi-Parting Slide Over Fixed Rooflight
Roof Access Door

Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 | info@nextgenrooflights.co.uk | www.nextgenrooflights.co.uk

