

The Pyramid & Lantern Rooflights - Opening

Detailed Description

Features:

Grade 6063-T6 Extruded Aluminium
Fully Thermally Broken
Polyester Powder Coating to Minimum
60 Microns
Suitable for Marine / Coastal Environments
Stainless Steel Concealed Fixings
Tested in accordance with the CWCT Standard
Air & Water Resistance 1050pa
Wind Load Resistance 2.0kN/m²



Usage:

Suitable for all nominally flat roof constructions and coverings e.g. Single Ply PVC, Fiberglass, lead, copper, zinc and other standing seams and asphaltic material.
Suitable for Green / Sedum Roofs

Product Guidance

Standard Sizes

Electric Operation - Wind, Rain & Temperature Sensors for auto-closing.
Remote Control

(mm)	Height	1000	1200	1400	1500	1700	2000
Width							
1000		✓	✓	✓	✓	✓	✓
1200		✓	✓	✓	✓	✓	✓
1400		✓	✓	✓	✓	✓	✓
1500		✓	✓	✓	✓	✓	✓
1700		✓	✓	✓	✓	✓	✓
2000		✓	✓	✓	✓	✓	✓
2200		✓	✓	✓	✓	✓	✓

Non-standard sizes and shapes are available on request

Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 | info@nextgenrooflights.co.uk | www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Vision AGI Limited, Company No. 08429446, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HF.



Standard Sizes

Manual Operation

(mm)	Height	1000	1200	1400
Width				
1000		✓	✓	✓
1200		✓	✓	✓
1400		✓	✓	✓

Non-standard sizes and shapes are available on request

NB: These are external kerb sizes.

Internal finished sizes; minus 200mm from above Width & Height dimensions

Standard Glazing Details:

6mm Toughened Outer
 18mm Warm Edge Spacer with 90% Argon Cavity
 6.8mm Laminate Low-e Inner
 Glass Centre Pane U-Value 1.1W/m²K

Enhanced glazing specifications incorporating thermal, acoustic, security, light transmission, solar gain, Class 2 Safety and decorative options are available, please contact manufacturer for details.

Standard Colour:

Internal – RAL 9010 Pure White Matt
 External – RAL 7015 Slate Grey Matt

Any RAL or BS colour can be specified

Seals:

Structural & Weather Seal – Low Modulus Silicone Sealant
 EPDM – UV & Water Resistant

Upstand:

To suit an overall finished Upstand of 100mm in width. Upstand by Next Generation Rooflights if required.

Warranty:

1 Year offered as standard.
 Extended warranty available as below, upon registration.

Glazing 10 Years
 Powder Coating 10 Years
 Mechanical Components 1 Year

Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 | info@nextgenrooflights.co.uk | www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Vision AGI Limited, Company No. 08429446, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HF.



Product Specification

Manufacturer:

- Name: Next Generation Rooflights
- Web: www.nextgenrooflights.co.uk
- Email: info@nextgenrooflights.co.uk
- Tel: +44 (0)1223 79 22 44
- Address: Queens Business Park, Wilbraham Road, Fulbourn, Cambridge, CB21 5GT

Product reference: The Pyramid & Lantern Rooflights - Opening

Other Rooflights in the Range

Fixed Skylight

Access Hatch Rooflight - Manual
Access Hatch Rooflight - Electric

Opening Rooflight - Electric
Opening Rooflight - Manual

Walk On Glass Floor - Internal Use
Walk On Glass Floor - External Use

Pyramid Rooflight - Manual
Pyramid Rooflight - Electric

Lantern Rooflight - Manual
Lantern Rooflight - Electric

Slide Over Roof Rooflight
Slide Over Fixed Rooflight
Bi-Parting Slide Over Roof Rooflight
Bi-Parting Slide Over Fixed Rooflight
Roof Access Door

Next Generation Rooflights

Queens Business Park, Wilbraham Road, Fulbourn, Cambridge CB21 5GT

01223 792 244 | info@nextgenrooflights.co.uk | www.nextgenrooflights.co.uk

Next Generation Rooflights is a trading name of Vision AGI Limited, Company No. 08429446, Registered Office: 1 Vicarage Lane, Stratford, London, E15 4HF.

